

——裁切线，不需印刷
 - - - -折线，不需印刷

Remark	Description	Editor	Date

封底 封面

Figure 4-2 The Side Panel

Table 4-2 Descriptions of the Side Panel

Interface/Buttons	Function
USB1*	Standard USB 3.0 interface, connected to a USB storage device, printer or 3G Dongle connection.
WiFi	WiFi dual-interfaces on/off button.

Interface/Buttons Function

WPS WPS Push Button, press this button to enable or disable the WPS function.

Rear Panel

Figure 4-3 shows the buttons on the rear panel of the ZHNN H6645P.

Figure 4-3 The Rear Panel

Table 4-3 Descriptions of the Rear Panel

Interface/Buttons	Function
Phone1	RS-11 port. It is used to connect to the phone through the telephone line.
Phone2	

Interface/Buttons Function

USB2* Standard USB 2.0 interface, connected to a USB storage device, printer or 3G Dongle connection.

WAN 2.5G RJ-45 port. It is used to connect to the uplink Ethernet access network.

LAN1 2.5G LAN2-LAN4 RJ-45 ports. It is used to connect the modem to computer, STBs or other network devices.

Power Power supply port. It is connected to the power adapter.

Reset Reset push button. During power on period, press this button for more than 5 seconds to reset the current settings to the factory default.

On/Off Power switch. Power on or power off the device.

*When the SFP uplink port is used, USB1 and USB2 cannot be used at the same time.

5 Hardware Connection

Figure 5-1 shows the devices that are connected to interfaces of the ZHNN H6645P.

Figure 5-1 Cable Connection

After the devices are connected to the ZHNN H6645P device, press the power button. When the corresponding indicators on the front panel are On, you can enjoy various services provided by the service provider.

The factors affecting the wireless network coverage range include the location of the product, distance between the product and a wireless terminal, number of obstacles, obstacle material and density, and interference source. It is recommended that you place the product in accordance with the following principles to maximize the strength of wireless signal.

- The product should be far away from the objects affecting wireless signal propagation, for example, an object with a high reflectivity such as a metallic object or a mirror.
- The product should be far away from an electrical appliance with a strong magnetic or electric field, for example, a microwave oven, a refrigerator, a wireless router, a cordless phone, or a Bluetooth product.
- The product should be installed on the same floor as the applied area.

6 Troubleshooting

The Power indicator on the front panel is off after the power button is pressed.

- The power switch does not turn on.
- The power adapter is not correctly connected to the device. Be sure to use the power adapter supplied with the device.

The LAN indicator on the front panel is off after the device is powered on.

- The corresponding LAN link is not established.
- The Ethernet cable is not correctly connected to the LAN interface.
- The network device connected to the LAN interface is not powered on.

The WAN indicator on the front panel is off after the device is powered on.

- The WAN link is not established.
- The Ethernet cable is not correctly connected to the WAN interface.
- Please contact the service provider for help.

Unable to connect to the network.

- Check that the Ethernet cable is correctly connected to the WAN interface and the Ethernet cable is correctly connected to the LAN interface.
- Check that the WAN indicator on the front panel is on and the Internet indicator on the front panel is solid green or flashing green.

Restore the factory default settings.

After the power is on, use a needle to press the button for over 5 seconds to restore the default factory settings.

ZHNN H6645P Home Gateway User Manual

CERTIFICATION CHECKER

DATE

ZTE

Address: ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, P.R.China

Postcode: 518057
 Tel: +86-755-2677 1900
 URL: http://support.zte.com.cn
 Email: support@zte.com.cn

ZTE CORPORATION

ZHNN H6645P Home Gateway User Manual

Manual No. 51-20210916095917-006
 Edition Time: 2022-05-27 (R1.0)

CE

LEGAL INFORMATION

Copyright © 2022 ZTE CORPORATION.

The contents of this document are protected by copyright laws and international treaties. Any reproduction or distribution of this document or any portion of this document, in any form by any means, without the prior written consent of ZTE CORPORATION is prohibited. Additionally, the contents of this document are protected by contractual confidentiality obligations. All company, brand and product names are trade or service marks, or registered trade or service marks, of ZTE CORPORATION or of their respective owners.

This document is provided "as is", and all express, implied, or statutory warranties, representations or conditions are disclaimed, including without limitation any implied warranty of merchantability, fitness for a particular purpose, title or non-infringement. ZTE CORPORATION and its licensors shall not be liable for damages resulting from the use of or reliance on the information contained herein.

ZTE CORPORATION or its licensors may have current or pending intellectual property rights or applications covering the subject matter of this document. Except as expressly provided in any written license between ZTE CORPORATION and its licensee, the user of this document shall not acquire any license to the subject matter herein.

ZTE CORPORATION reserves the right to upgrade or make technical change to this product without further notice.

Users may visit ZTE technical support website: <http://support.zte.com.cn> to inquire related information.

The ultimate right to interpret this product resides in ZTE CORPORATION.

1 Safety Precautions

Note

The users should read the usage cautions above carefully and will be responsible for any incident resulting from the violation of the above cautions.

Usage Cautions

- Read all the safety cautions carefully before using the device.
- Only use the accessories included in the package, such as power supply adapter.
- Do not extend the power cord, otherwise the device will not work.
- The power supply voltage must meet the requirements of the device input voltage (The voltage fluctuation range is less than 10%).
- Keep the power plug clean and dry to prevent any risk of electric shock or other dangers.
- Disconnect all the cables during a lightning storm to prevent the device from damage.
- Power off and unplug the power plug when the device is not in use for a long time.
- Do not attempt to open the covers of the device. It is dangerous to do so when the device is powered on.
- Power off and stop using the device under the conditions such as, abnormal sound, smoke, and strange smell. Contact the service provider for maintenance if the device is faulty.

Environment Requirements

- Ensure proper ventilation to the device. Place the device away from direct sunlight.
- Keep the device ventilated and dry. Never spill any liquid on the device.
- Do not place any object on the device to prevent any deformation or damage to the device.
- Do not place the device near any source of heat or water.
- Keep the device away from any household appliances with strong magnetic or electric fields, such as microwave oven and refrigerator.

Cleaning Requirements

- Before cleaning, power off the device, and unplug all the cables connected to the device, such as power cable, optical fiber, and Ethernet cable.
- Do not use any liquid or spray to clean the device. Use a soft dry cloth.

Environment Protection

- Do not dispose the device or battery improperly.
- Observe the local regulations about the equipment disposal or treatment.

Restrictions in the 5 GHz Band

According to Article 10(10) of Directive 2014/53/EU, the packaging shows that this radio equipment will be subject to some restrictions when placed on the market in Belgium(BE), Bulgaria(BG), the Czech Republic(CZ), Denmark(DK), Germany(DE), Estonia(EE), Ireland(IE), Greece(EL), Spain(ES), France(FR), Croatia(HR), Italy(IT), Cyprus(CY), Latvia(LV), Lithuania(LT), Luxembourg(LU), Hungary(HU), Malta(MT), Netherlands(NL), Austria(AU), Poland(PL), Portugal(PT), Romania(RO), Slovenia(SL), Slovakia(SK), Finland(FI), Sweden(SE), Turkey(TR), Norway(NO), Switzerland(CH), Iceland(IS), and Liechtenstein(LI).

The WLAN function for this device is restricted to indoor use only when operating in the 5150 to 5350 MHz frequency range.

RF Exposure Information

The Maximum Permissible Exposure (MPE) level is calculated based on a distance of 4~20 cm between the device and the human body. To maintain compliance with the RF exposure requirement, a separation distance of 20 cm between the device and the human should be maintained.

EU Declaration of Conformity

Hereby, ZTE Corporation declares that the radio equipment type ZHNN H6645P is in compliance with Directive 2014/53/EU. The full text of the EU declaration of conformity is available at the following Internet address:
<http://support.zte.com.cn/support/ce/eu/>

Environmental Information

The equipment you purchased has required the extraction and use of natural resources for its production. It may contain substances that are hazardous to people's health and to the environment. To avoid putting such substances into our environment and to reduce pressure on our natural resources, we ask that you reuse or recycle your end-of-life equipment by using an accredited electronics take-back system.

The symbols below indicate that this product should be reused or recycled and not simply discarded. Please locate and use an appropriate reuse and recycling site. If you need more information on collection, reuse and recycling systems, contact your local or regional waste administration. You may also contact your equipment provider for more information on the environmental performances of these products.

D.Lgs. 03.09.20 n.116.
 Raccolta differenziata famiglia di materiali- PLASTICA.
 Verifica le disposizioni del tuo comune.

2 Package Check

Please ensure the ZHNN H6645P package contains the following items.

Name	Quantity
ZHNN H6645P	1
Power Adapter	1
RJ-45 Ethernet Cable	1
RJ-11 Telephone Cable	1
User Manual	1

Note

The list is only for reference. The actual contents may vary from the list.

If any of the items included in the package is incorrect, lost or damaged, please contact your service provider. If you need to replace the product, please keep the package and all the items in good condition.

3 Product Specifications

Table 3-1 describes the product specification of the ZHNN H6645P.

Table 3-1 Product Specification

Technical Specifications	
Dimensions	198 mm (H) × 263 mm (W) × 65 mm (D)
Power adapter	Input: AC 100 V ~ 240V, 50 Hz/60 Hz Output: DC 12.0V, 2.5 A
Environment Requirements	
Operation temperature	0 °C to 40 °C (32 °F to 104 °F)
Storage temperature	-40 °C to 70 °C (-40 °F to 158 °F)
Operation humidity/Storage humidity	5% ~ 95% (non-condensing)
Wi-Fi Radio Specifications	
Radio Frequencies	Maximum Output Power
Wi-Fi 2.4 GHz band:	ERP < 20 dBm
2414 MHz~2472 MHz	
Wi-Fi 5 GHz band:	ERP < 23 dBm
5150 MHz~5330 MHz	
Wi-Fi 5 GHz band:	ERP < 30 dBm
5450 MHz~5725 MHz	

Figure 4-1 The Front Panel

Table 4-1 describes the indicators on the front panel of the ZHNN H6645P unit.

Table 4-1 Descriptions of Indicators

LED Indicator	Status	Description
POWER	Off	The device is powered off.
	Solid green	The device is powered on properly.
	Flashing green	The device is booting.
	Solid red	The device is performing self-detection or the self-detection fails.
WAN(Ethernet)	Flashing red	The device is upgraded remotely or locally.
	Off	The equipment is not powered on or the WAN port is disabled.

LED Indicator	Status	Description
WAN (SFP Optical Link)	Solid green	The Ethernet connection has been established.
	Off	The equipment is not powered on, the SFP module is not inserted or no optical fiber is detected.
5G	Solid green	The 5G SFP uplink physical link negotiation has been established.
	Off	The gateway is switched off.
INTERNET	Solid green	The WAN connection is online. The device has a WAN IP address from DHCP, DHCP or statically configured. LED remains green in the case of disconnection due to idle timeout when PPPoE dial-on-demand is enabled. Green LED indicates that the routing connection state is up.
	Solid red	The WAN connection is dialing up or fails to get online. Device attempted to become IP connected and failed (no DHCP response, no PPPoE response, PPP authentication failed, no IP address from DHCP, etc).
	Flashing green	The Internet connection has been established and the data is being transmitted or received.
LAN	Off	The LAN connection has not been established.
	Solid green	The LAN connection has been established.
2.4G	Flashing green	Data transmission is in processing. The indicator flashes according to the LAN traffic.
	Off	WLAN RF switch is off.
2.4G	Solid green	WLAN RF switch is on.

LED Indicator	Status	Description
PHONE	Flashing green	WLAN RF switch is on and the data is being transmitted or received, and the flashing frequency indicates Wi-Fi network traffic.
	Off	WLAN RF switch is off.
PHONE	Solid green	WLAN RF switch is on.
	Flashing green	WLAN RF switch is on and the data is being transmitted or received, and the flashing frequency indicates Wi-Fi network traffic.
PHONE	Off	The device has not been registered to the VoIP network.
	Solid green	The device has registered to the VoIP network.
PHONE	Flashing green	The associated telephone is off-hook.
	Off	No WPS access or the WPS access of the terminal exceeds 5 minutes.
WPS	Solid green	WPS access is successful. This indicator will be automatically off after 5 minutes.
	Flashing slowly green	WLAN terminal is in WPS accessing process.
WPS	Flashing fast green	The WPS accessing of the WLAN terminal is faulty.

Side Panel

Figure 4-2 shows the buttons and interfaces on the side panel of the ZHNN H6645P.

对折线

NOTES (技术要求) :

- Dimension after folding(折叠尺寸): 97*139mm ;
- Printing colour(印刷颜色): black printing(黑色);
- Material(材质): 70g writing paper(70g书纸);
- Coating(表面处理): 无
- Binding process(装订工艺): paper folding(折页)---对折后再包心折
- Output lpi(输出网线): 200lpi;
- Tolerance(公差): 长(L)*宽(W)± 1.0mm;
- Raw materials and the corresponding post processing should meet requirements defined in the T&W Environmental Protection Technical Standards (原材料及后处理工艺均能满足我司《环保技术标准》要求.)

DIM	TOL±	C1	C2	C3	C4
RANGE					
0~6		0.1	0.1	0.15	0.2
6~30		0.2	0.3	0.4	0.5
30~80		0.25	0.5	0.9	1.2
80~180		0.3	0.8	1.2	1.5
180~315		0.5	1.3	1.8	3
315~500		0.7	1.5	2.5	4
500~800		0.9	1.8	3	5
ANG.TOL±		0°~30°/0.1°	30°~60°/0.3°	60°~90°/0.5°	

CUSTOMER: ZTE		MODEL: ZHNN H6645P		PART NO: 6100000xxxx	
TITLE: 用户手册	UNIT'S mm	VER: V01	SCALE N/A	DRAW CHECK	DATE: 2022-7-29
FINISH /	SHEET 1/1	PDE	N/A		